

Bitumen Washing Machine

For the removal of bitumen residues and small parts and glassware with non-flammable solvents trichloroethylene (TRI), perchloroethylene (PER, Tetra) or methylene chloride (methylene) in a closed cycle.

- ▶ Heated washing area approx. 500 x 300 x 300 mm with spray nozzles for internal and external cleaning of up to 8 RTFOT glasses/PAV Pans, Round Bottom Flasks
- ▶ Collecting sieve at the solvent drain for coarse soiling
- ▶ Integrated distillation at the solvent tank and residue tank
- ▶ Integrated recirculating air drying at the end of the process
- ▶ Variable process control via integrated SPS with variable cleaning and drying times
- ▶ Connections for solvent supply and disposal
- ▶ Various insert racks optionally available

Technical data

Dimensions	1030 x 780 x 1280 mm
Weight	196 kg
Electrical data	3/N/PE, 240 V, 60 Hz, 4kW

20-5010

20-5010-60


Bitumen Washing Machine 60 Hz

Advantages:

- ▶ Closed solvent cycle
- ▶ Different accessories possible
- ▶ Easy programming
- ▶ Increased efficiency of the workflow through an uncomplicated and quick purification



TIP



Clean RTFOT glasses easy and quick in the Bitumen Washing Machine or in our Asphalt Analyzers.

Insert basket for small parts

20-5010E10

